


27 g



[100% polycarbonate]



### >> Uses (\*)

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, carpentry, polishing, industry, laboratories, sports etc ... UV protection.

### >> Technical features

- ✓ Safety visitor spectacle. Large ventilated sidearms. Screen and sidearms in clear polycarbonate. No metallic part. Attachment points on side arms for neck cord.
- ✓ **Lens thickness:** 2.00 mm.
- ✓ **Dimensions:** (length) 150 mm x (width) 140 mm.
- ✓ **Weight:** 27 g.
- ✓ **Packing:** - Carton of 100 pairs.  
- Box of 10 pairs.  
- Each pair under individual polybag.



Learn more [www.singer.fr](http://www.singer.fr)

### >> Advantages

- ✓ Light weight and comfortable wear.
- ✓ Ventilated sidearms.
- ✓ Large peripheral vision.
- ✓ Reliability of an **ISO 9001** system in production.
- ✓ Perforated temples will allow the use of adjustable cord.

### >> Conformity

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection (EN166)	Symbole <b>FT</b>	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality (EN166)	Symbole <b>1</b>	Class 1: continuous works (better quality).
Scale number (EN170)	Symbole <b>2C-1.2</b>	Colour perception: not impaired Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor. This applies to UVC and most UVB radiation <sup>(b)</sup> . Typical source <sup>(a)</sup> : Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps. <i>(a) The example given for typical source is for general guidance.</i> <i>(b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm &amp; 100 nm to 280 nm for UVC).</i>

Your distributor **SINGER® SAFETY**

