



1,20 kg

Made under



10.00 m Ø 12 mm



>> Type of use (\*)



Light industry Heavy industry Structural works Maintenance Public works

>> Technical features

- ✓ Braided polyester rope.
- ✓ Compatible with the mobile fall arrester on rope STOPRO.
- ✓ Not compatible with the mobile fall arrest system STOPLUX.
- ✓ Diameter: 12 mm.
- ✓ Length: 10 meters.
- ✓ Weight: 1.20 kg.
- ✓ Packing:

- carton of 10 units.
- boxes of 1 unit.



Learn more: [www.singer.fr](http://www.singer.fr)



>> Advantages

- ✓ One termination with splices protected with a plastic sheath and loop with plastic reinforcement thimble. This prevents the rope from being damaged by the metallic contact of a connector.
- ✓ Also available in 20 meters length (ref: ASSULINE200).
- ✓ ISO 9001 certified manufacturing.



EN 353-2: 2002

CE 0598

>> Conformity

This product has been tested according to the following European standard:

- **EN 353-2: 2002.** Personal Protective Equipment Against Falls From A Height.-  
Part 2: Guided Type Fall Arresters Including A Flexible Anchor Line

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.** EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body n°2777. The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body n°0598.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS\_2020.06.24. Copyright: Singer, Förlia.