



Made under

1,40 kg

10.00 m Ø 14 mm



>> Type of use (*)

Light industry Heavy industry Structural works Maintenance Public works



>> Technical features


- ✓ Anchorage line made of stranded polyamide rope.
- ✓ Compatible with the mobile fall arrester on rope STOPRO.
- ✓ Diameter: **14 mm**.
- ✓ Length: **10 meters**.
- ✓ Weight: **1,40 kg**.
- ✓ Packing:
 - carton of 10 units.
 - boxes of 1 unit.



Learn more: www.singer.fr

>> Advantages

- ✓ Each end with abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- ✓ Each termination is spliced and is protected with a strong transparent covering sleeve which not only protects the end but also make the splicing visible for easy inspection before to use.
- ✓ Coloured tracer yarn with loses its colour in due course of time, to show that the rope is now unfit for further use.
- ✓ **ISO 9001** certified manufacturing.



>> Conformity

This product has been tested according to the following European standard:
 - **EN 353-2: 2002**. Personal Protective Equipment Against Falls From A Height.-
 Part 2: Guided Type Fall Arresters Including A Flexible Anchor Line

EN 353-2: 2002
CE 0598

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III**.
 EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body **n°2777**.
 The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**.
 Notified body **n°0598**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS_2020.06.24. Copyright: Singer, Fiolia.