Leather gloves - Drivers



<u>CHV114HB</u>

Fine

This cow leather glove with water repellent treatment is particularly suitable for all kinds of light handling in a wet environment. Handling of materials, handling with tools (pickaxes, shovels,

drills, sanders...), maintenance of green spaces, etc. For bricklayers, carpenters, gardeners, farmers, logisticians, carriers.

>>Technical features

- Full goatskin leather.Water repellent leather.
- Elasticated knitted wrist.Leather vein patch.
- Buttonhole. Gunn cut pattern.
- Wing thumb.
- Color : beige.
- ✓ Sizes: 8, 9, 10, 11.
- Packing: carton of 100 pairs. - bundle of 10 pairs.

Learn more: www.singer.fr

iso 900

Made

under

>> Advantages

- Knitted wrist preventing from the penetration of foreign bodies and providing a good hand fit.
- Comfort and softness of the grain.
- ✓ Very good dexterity.
- Can be used as cover glove.
- Water resistant treatment for duties even in humid environment while you benefit from the traditionnal comfort and advantages of the natural leather.
- Very comfortable wear.
- ISO 9001 certified manufacturing.

>> Conformity

This glove has been tested according to the following European standards :

- EN 420 : 2003 + A1 : 2009. Protective gloves General requirements and test methods.
- EN 388 : 2016. Protective gloves against mechanicals risks.

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category II. EU type examination certificate (module B) issued by SGS, notified body n°0120.

EN 388: 2016. Protective gloves against mechanical risks Mechanical data. Level Level Niveau Level Levels EN 388 : 2016 Level Information about levels. 1 2 3 4 5 ▼ 100 500 2000 8000 _ 2 Abrasion resistance (number of cycles) Blade cut resistance (index) 1,2 2,5 5.0 10,0 20,0 0 25 10 50 75 2 Tear resistance (in Newtons) _ 20 100 1 Perforation resistance (in Newtons) 60 150 _ 2021X Cut resistance (as per EN ISO13997) Level Level Level Level Level Level Level В С D Е F А (TDM test) 2 5 10 15 22 30 Х «X» means that the glove has not been submitted to the test.

Your distributor SINGER[®] SAFETY



work in a damp environm (F