

SNR
23,0dB

WEIGHT
261g

Made under
ISO 9001



>> Type of use (*)

When worn properly and given adequate care, this equipment provides excellent protection by filtering high frequency noise encountered with dynamic machine such as workshop equipment, motor saws..

Industry, construction, maintenance of green spaces, foresters...

>> Technical features

- ✓ Slot fitting ear defenders.
- ✓ Suitable for easy fitting to helmets HG902.
- ✓ Soft foam filled black ear-cushions.
- ✓ Two-colored: black and yellow.
- ✓ Adapters also allow you to slide if necessary a complementary visor holder (HG867) and polycarbonate protective visors (ACC805, ACC805LARG) or mesh visors (HG825L).
- ✓ **Weight:** 261 g.
- ✓ **Packing:** - carton of 60 pieces.
- bundle of 1 piece.



Learn more: www.singer.fr

>> Advantages

- ✓ Combined protection with an helmet.
- ✓ Comfort and softness of wear even during long use.
- ✓ Good and regular fit all around the ear.
- ✓ Easy to snap on and off from safety helmet.
- ✓ Allow a complementary protection of the face with visor holder HG867.

>> Conformity

This product has been tested according to the following European standard:

- **EN 352-3: 2002.** Hearing protection. Part 3: Ears-muffs attached to industrial safety helmet.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.** EU type examination certificate (**module B**) issued by **BSI (Netherlands)**. Notified body **n°2797**

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **BSI**. Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Values of sound attenuation

SNR value in accordance with ISO / DIS 4869-2 with parameter $\alpha = 1$

SNR value : **23,0 dB (H = 28,0 dB M = 20,0 dB L = 12,0 dB)**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	12.2	10.3	15.2	23.9	32.3	35.2	31.0	27.2
Standard deviation	6.0	5.2	5.6	5.3	4.9	5.0	3.5	3.7
APV (dB)	6.2	5.1	9.6	18.6	27.5	30.2	27.5	23.6



Your distributor **SINGER® SAFETY**

