

>> Type of use (*)

Thanks to its technical features, this glove is particularly suitable for all heavy works requiring good strength as well as good resistances in oily and / or fatty environments: automobile assembly, automobile repair, construction, public works, metal works, raw material handling, sharp handling sheets, household refuse collection, handling abrasive materials, deep sea fishing, maintenance of public parks...

>> Technical features

- → Montage / matières: Cut and sewn liner. Nitrile fully coated. Heavy coating. 100% cotton fleece liner. Knitted wrist.
- → Color: natural liner / blue coating.
- ✓ Sizes: 8, 9, 10.
- → Packing: carton of 100 pairs.
 - bundle of 10 pairs.



Learn more: www.singer.fr

>> Advantages

- → Heavy coating on a fleece lining for a maximum protection and comfort.
- → Fully coated for work applications even in wet environnments.



>> Conformity

This glove has been tested according to the following European standards :

- EN 420: 2003 + A1: 2009. Protective gloves General requirements and test methods.
- EN 388: 2016. Protective gloves against mechanicals risks.

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category II.

EU type examination certificate (module B) issued by the CTC. Notified body n°0075.

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Le	vels ▼
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	1	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	Х

Your distributor SINGER® SAFETY





