



16 mm



165 g

>> Type of use (\*)



Light industry



Heavy industry



Structural works



Maintenance



Public works



>> Technical features

- ✓ Steel symmetrical connector, screw closure.
- ✓ With a wide ferrule. Perfect to connect fall arrest equipment.
- ✓ Non-closing red indicator.
- ✓ **Class B** (basic connector)
- ✓ **Class M** (multi-use connector)
- ✓ Opening: **16 mm**.
- ✓ Weight: **165 g**.
- ✓ **Packing:** - carton of 50 pieces.  
- box of 10 units.



Learn more: [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ Non-closing red indicator to ensure safety.
- ✓ Incorporates «No hook» technology.
- ✓ **ISO 9001** certified manufacturing.



>> Conformity

This product has been tested according to the following European standard:  
**EN 362: 2004**. Personal protective equipment against falls from a height. **Connectors**.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III**.  
EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body **n°2777**.  
The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body **n°0598**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**

