PVC dipped - Cut and sewn liner



>> Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all major heavy works in wet environments.

Industry, transport, agriculture, construction, public works, masons, painters...

>> Technical features

- ✓ 100% cotton interlock cut and sewn liner.
- ✓ Palm and knuckle P.V.C coating.
- Simple dipped.
- Open back (ventilated).
- ✓ Knitted wrist.
- ✓ Red colour.
- ✓ Sizes: 9 and 10.
- Packing: carton of 100 pairs.
 bundle of 10 pairs.

Learn more: www.singer.fr



CE

>> Advantages

The guarantee and benefits of an ISO 9001 certified manufacturing: quality of products, regularity...

- ✓ Quality of the PVC coating, soft and resistant.
- Increased ventilation provided by the open back.
- Good value for money.

>> Conformity

This glove has been tested according to the following European standards :

- EN 420 : 2003 + A1 : 2009. Protective gloves General requirements and test methods.
- EN 388 : 2016. Protective gloves against mechanicals risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category II**. EU type examination certificate (module B) issued by **SATRA (Irland)**. Notified body **n°2777**. Download the EU declaration of conformity on: http://docs.singer.fr

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼ 4 1 1		EN 388 : 201
Abrasion resistance (number of cycles)	100	500	2000	8000	-			
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0			║╽┎╞═
Tear resistance (in Newtons)	10	25	50	75	-			
Perforation resistance (in Newtons)	20	60	100	150	-	1		
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level	Level B	Level C	Level D	Level E	Level F	Level	4111X
	2	5	10	15	22	30	Х	

Your distributor SINGER® SAFETY

