



>> Type of use (*)

* Recommended for manual welding techniques with light formation of platters and drop e.g gas welding, TIG welding, MIG welding, micro plasma welding, brazing, spot welding, MIMA welding (with rutile covered electrode) for operation of machine e.g oxygen cutting machines, plasma cutting machines, machines for thermal spraying, bench welding.

This clothing is intended to protect against flames molten metal splatter, radiant heat and short term, accidental electrical contact.

(more information and uses: please check the user information enclosed with the product).

>> Technical features

- ✓ Safety jacket for welders.
- ✓ Sizes M, L, XL.
- ✓ Cow split leather.
- ✓ Back in Proban® treated fabric.
- ✓ Length: 80 cm.
- ✓ Long sleeves.
- ✓ Straight collar.
- ✓ Fastening with snaps under leather flap.
- ✓ Sewn with aramid yarn.
- ✓ Colour: natural.
- ✓ Packing: - carton of 5 pieces.
- bundle of 1 piece. 

Learn more: www.singer.fr

>> Advantages

- ✓ Thick and strong split leather hide.
- ✓ Light weight Proban® fabric back.
- ✓ With aramid yarn for a good resistance of seams.

>> Compliance

This garment has been tested according to the following European Standards (**Category II**).

- **EN ISO 13688: 2013.** Protective garment. General requirements.
- **EN ISO 11611: 2007.** Protective clothing for use in welding and allied processes.

It complies with the European Regulation **(EU) 2016/425** on Personal Protective Equipment (**PPE**).
EU examination type certificate (**module B**) issued by **INTERTEK**. Notified body **n°0362**.



ISO 11611:2007 specifies two classes with specific performance requirements, i.e. Class 1 being the lower level and Class 2 the higher level.

- Class 1 is protection against less hazardous welding techniques and situations, causing lower levels of spatter and radiant heat.
- Class 2 is protection against more hazardous welding techniques and situations, causing higher levels of spatter and radiant heat.

The letter A1 or A2 corresponds to the method of test used for the limited flame spread, according to ISO 15025:2000 standard.

Your distributor **SINGER® SAFETY**