P.V.C dotted - Seamless knitted liner

>> Type of use ^(*)

Thanks to its technical characteristics, this glove is particularly suitable for all light handling, fine works... Packaging, shipping & receiving, automotive assembly, electronic industry, assembly shops, handling cartons, boxes, frames...

TCC507

CE

For forklift drivers, warehouse keepers, removal men...

>> Technical features

- Construction: seamless knitted.
 Elasticated wrist. Dotted palm.
- ✓ Liner: polyester/cotton fibres.
- ✓ Gauge: 7.
- ✓ Coating: P.V.C dotted palm and back.
- Colour: white liner, blue dots.
 Sizes: men's (9) = TCC507HB.
 - ladies' (8) = TCC507FB.
 - Packing: carton of 100 pairs.
 bundle of 10 pairs.

Learn more: www.singer.fr

>> Main advantages

- Seamless construction: improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity and reduces hand fatigue.
- Polyester/cotton fibres: the polyester fibres offer good tensile strength, it provides good ensistance against abrasion; it is resistant against mold and fungus. It is low water absorbent.
 Cotton provides the comfort of a natural material which enhances the absorption of sweat and does not irritate the skin.
- Open back for better ventilation and improved softness.
- Elasticated knitted wrist for a snug fit.
- P.V.C dotting: the P.V.C dotting on palm & back (reversible style) will bring you better grip during handling.
- ISO 9001 certification for a regular and good quality of products.

>> Conformity

This glove has been tested according to the following European standards :

EN 420 : 2003 + A1 : 2009. Protective gloves - General requirements and test methods.
EN 388 : 2016. Protective gloves against mechanicals risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category II.** EU type examination certificate (module B) issued by **SATRA (Irland).** Notified body **n°2777.** Download the EU declaration of conformity on: http://docs.singer.fr

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Le	evels ▼	EN 388 : 2	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	1 1 2			
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0			╵╿┎╞	
Tear resistance (in Newtons)	10	25	50	75	-				
Perforation resistance (in Newtons)	20	60	100	150	-	1			
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level	1121	
«X» means that the glove has not been submitted to the test.	2	5	10	15	22	30	X		

Your distributor SINGER® SAFETY

