



>> Use (*)

Thanks to a careful workmanship and a strict selection of materials, this equipment can be used for indoor or outdoor work activities, for many jobs in the industry, logistics, transport, parks maintenance, crafts or building and public works...

>> Technical features

- ✓ Low cut safety shoes
- ✓ Water repellent full grain leather, metal hooks.
- ✓ 200J shockproof composite toe cap.
- ✓ E.F.P tongue.
- ✓ Ergonomic insole preformed in PU.
- ✓ High strength textile puncture resistant midsole.
- ✓ Double-density polyurethane sole.
- ✓ Brown colour, grey stitching.
- ✓ Sizes : 39 to 47.
- ✓ Packing : Carton of 10 pairs.
Bundle of 1 pair.



Learn more : www.singer.fr




680g⁽¹⁾

⁽¹⁾Approximative weight of a shoe (smaller size)

>> Advantages

- ✓ ISO 9001 certified manufacturing.
- ✓ 3 flex zones on the sole for an optimal flexibility.
- ✓ Energy absorbing heel.
- ✓ Features the «**comfort pack**»: with anatomical insole, **E.F. P** tongue = more comfort for the plantar arch and less fatigue every day.
- ✓ Unique **Ergonomic Foam Protect (E.F.P)** system on collar: design & materials specifically designed to minimize compression, stabilize the lacing in order to provide optimum comfort and support.



>> Compliance

This safety shoe has been tested according to the following European Standard.

- **EN ISO 20345: 2012.** Personal protective equipment - Safety footwear.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). (**Category II**)

EU type examination certificate (**module B**) issued by **INTERTEK Italia Spa**. Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol S3	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol SRC	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your distributor **SINGER® SAFETY**

