



>> Type of use (*)



Light industry



Heavy industry



Structural works



Maintenance



Public works

>> Technical features

- ✓ Work positioning lanyard.
- ✓ 3 strand polyamide rope.
- ✓ Length: **2,00 m**.
- ✓ Diameter: **14 mm**.
- ✓ Automatic grip adjuster for length adjustment.
- ✓ Equipped with 2 karabiners.
- ✓ Packing:

- carton of 10 pieces.
- bundle of 1 piece.



Learn more: www.singer.fr

>> Advantages

- ✓ To guarantee the best quality, the production line of SINGER® Safety is integrated.
- ✓ We control and produce in a single factory of over 10,000 m² the creation and fabrication of the products:
 - Weaving coated thread into straps,
 - Stamping metal pieces and chemical treating,
 - Harness assembly,
 - Individual control and real-time testing thanks to the different laboratory devices and tools, etc.



>> Conformity

This product has been tested according to the following European standard:

- **EN 358: 1999**. Personal protective equipment against falls from a height.

«Belts for work positioning and restraint and work positioning lanyards».



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III**.

EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body **n°0277**.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body **n°0598**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**

