



## Area of use\*



LIGHT INDUSTRY

FINISHINGS

MAINTENANCE

TRANSPORT

LOGISTICS

## Technical features

**Metal free, low cut safety shoes.**

**Upper:** reinforced fabric (polyester).

**Lining:** textile.

**Tongue:** comfortable padding, with gusset.

**Toe cap:** composite shockproof 200J.

**Insole:** ergonomic in preformed PU.

**Pierce resistant midsole:** high tenacity textile.

**Sole:** polyurethane double-density.

**Colour:** blue, orange and black.

**Sizes:** 36 to 47.

**Packaging:** carton of 10 pairs.

**Subpackaging:** individual box.

**Weight:** 550 g (Approximative weight of a shoe, size 42).



## Advantages

**Suitable for all users** with a wide choice of shoe sizes.

**Flexibility and protection** thanks to pierce resistant midsole made of high tenacity textile.

**High resistance** thanks to composite shockproof toe cap

**Metal free shoes.**



**FOOT**  
Protection

## Certification

This product complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II**. Issued by **TUV RHEINLAND**, notified body n°0197.

**EN ISO 20345 : 2022 (S1 PS FO SR)**



Download the EU declaration of conformity on <http://docs.singer.fr>

## STANDARDS (2022)

EN ISO 20344	Personal protective equipment: Test methods for footwear.
EN ISO 20345	<b>Safety footwear:</b> Toe protection against shocks (200 J) and the risks of flattening (15 kN).
EN ISO 20346	Protective shoes: Toe protection against shocks (100 J) and the risks of flattening (10 kN).
EN ISO 20347	Occupational footwear: No specification about toe protection.

## SLIP RESISTANCE

SB	Basic properties	On ceramic surface, covered with SLS.
SR	Optional properties	On ceramic surface, covered with glycerol.

## EN ISO 20345 - SHOES CLASS

SB	Class I ou II	Basic properties
S1	Class I	SB + Closed backpart + Antistatic shoes (A) + Energy absorption of the heel (E)
S2	Class I	S1 + Water penetration and absorption resistance of the upper (WPA)
S3	Class I	S2 + Metal pierce resistant midsole (P) + Studded sole
S3L	Class I	S2 + Metal free, pierce resistant midsole (PL) + Studded sole
S3S	Class I	S2 + Metal free, pierce resistant midsole (PS) + Studded sole
S6	Class I	S2 + Water resistance of the whole footwear (WR)
S7	Class I	S3 + Water resistance of the whole footwear (WR)
S7L	Class I	S3L + Water resistance of the whole footwear (WR)
S7S	Class I	S3S + Water resistance of the whole footwear (WR)
S4	Class II	SB + Closed backpart + Antistatic shoes (A) + Energy absorption of the heel (E)
S5	Class II	S4 + Metal pierce resistant midsole (P) + Studded sole
S5L	Class II	S4 + Metal free, pierce resistant midsole (PL) + Studded sole
S5S	Class II	S4 + Metal free, pierce resistant midsole (PS) + Studded sole

## USED MATERIAL CLASS

Class I	All leather and other materials (except for all rubber or all polymer)
Class II	All rubber (fully vulcanised) or all polymer (fully moulded).

## EN ISO 20345 - OPTIONAL REQUIREMENTS











E	Energy absorption of the heel
P	Metal pierce resistant midsole
PL	Metal free, pierce resistant midsole (tested with broad tip)
PS	<b>Metal free, pierce resistant midsole (tested with fine tip)</b>
CR	Cut resistant upper
M	Shockproof metatarsal protection
C	Conductive shoes
A	<b>Antistatic shoes</b>
HI	Insulation sole against contact heat
CI	Insulation sole against cold
HRO	Contact heat resistant outsole compound
WPA	Water penetration and absorption resistance of the upper
WR	Water resistance of the whole footwear
AN	Malleoli protection
SC	Stone guard resistance to abrasion
SR	<b>Slip resistance (ceramic surface + glycerin)</b>
FO	<b>Resistance to fuel oil</b>
LG	Grip system for ladder

## EN 61340-4-3 - ELECTROSTATIC (ESD)

Shoes that cover this standard are «dissipative». This standard defines the shoes that protect electronic equipment against an electrostatic discharge.

Electrical resistance: < 1 Ω x 10<sup>6</sup>. Antistatic shoes are not necessarily ESD.

## ADVANTAGES

	<b>Slip resistance</b>		<b>Studded sole</b>
	Antiperforation steel sole (1100N)		<b>Antiperforation high tenacity textile sole (1100N)</b>
	Shockproof steel toe cap (200J)		<b>Shockproof composite toe cap (200J)</b>
	<b>Antistatic properties</b>		Water penetration resistance
	<b>Resistance to fuel oil</b>		<b>Energy absorption of the heel</b>